

4

3

2

1

INNER RING

43.0 mm
[1.693 in]

39.7 mm
[1.563 in]

2.5 mm
[.100 in]

SECTION A-A

B



Ø51.3 mm
[2.020 in]

Ø46.2 mm
[1.820 in]

Ø38.1 mm
[1.500 in]
CLEAR
APERTURE

Ø2.4 mm
[.094 in]

TF112-XXXX

A

A

1.8 mm
[.070 in]

FILM
SURFACE


DETAIL B

SERIAL NUMBER ENGRAVED PRIOR TO ANODIZE
 ANODIZED PER MIL 8625 TYPE II CL II BLACK STANDARD
 CUSTOM APERTURES AVAILABLE UPON REQUEST

		Frame Options	
Frame	Aperture	Material	Finish
TF-112	38.1mm (1.50")*	Al=6061 Aluminum*	BA=Black Anodize*
		SS=304 Stainless	NA=No Anodize
		Cu=Copper	

* Standard

How to order example: TF112-38.1-Al-BA

DRAWN JLDG	1/7/2009	 Luxel Corporation PO Box 1879, 515 Tucker Ave. Friday Harbor, WA 98250 www.luxel.com 360-378-4137 fax: 360-378-4266						
CHECKED								
MATERIAL *6061 T651 Al		TF112 Standard Filter Frame						
UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MILLIMETERS TOLERANCES ON:		<table border="1"> <tr> <td>SIZE C</td> <td>DWG NO TF112S</td> <td>REV A</td> </tr> <tr> <td colspan="2">SCALE</td> <td>SHEET 1 OF 1</td> </tr> </table>	SIZE C	DWG NO TF112S	REV A	SCALE		SHEET 1 OF 1
SIZE C	DWG NO TF112S	REV A						
SCALE		SHEET 1 OF 1						
DECIMALS: .X = ± 0.5 .XX = ± 0.25 .XXX = ± 0.13 ⁰ ANGLES = ± .25°								

4

3

4

2

1

D

D

C

C

B

B

B

B

A

A